

2,500 CFM ELECTRIC POWERED PORTABLE DUST COLLECTOR

FEATURES

- AIR VOLUME: 2,500 ACFM at - 8" W.G.

- POWER SOURCE:

5HP, 230/460 volt, 3 phase, TEFC motor, 5 HP rated enclosed motor starter with 120 VAC controls, pre-wired plug @ 15 ft

- 3 STAGE FILTRATION:
 - Cyclonic separator
 - Stainless steel wire mesh pre-filter, spark arrestor
 - (2) Nanofiber cartridge media, fire retardant, MERV 15, 520 sq. ft. media, 99.97% @ 0.3 micron
 - Carbon odor discharge filter

STANDARD EQUIPMENT

- (1) 8" QF inlet hose connection with 6" QF reducer
- Adjustable 55 gallon drum adapter (drum not included)
- (4) 5" diameter casters, swivel locking
- Manual push button cartridge pulse jet cleaningInlet air regulator with gauge
- Magnehelic gauge
- Dust and debris dropout drawer
- 12 gauge carbon steel construction
- Epoxy primer and polyurethane enamel top coat

OPTIONS

- 120/230 volt, 1 phase, TEFC motor
- Gasoline engine power source
- On-Board air compressor packageCompressor cold weather kit
- Sound package for ultra quiet operation
- HEPA filter mediaPoly paint pad pre-filter
- Refillable carbon tray filter
- Explosion proof options NEMA 7/9
- Automatic timed pulse jet cleaning
- Fork pockets or single lift point
- Bulk bag unloading attachment
- 55 gallon drum lifting and pivot clamp







2500 CFM ELECTRIC POWERED PORTABLE DUST COLLECTOR





Weight -1,500 lbs.