



RAPID PREP

DH/AC 5000 HP

FEATURES

SKID MOUNTED

Four (4) - four way fork truck tubes large enough for an 8 ton fork truck

STACKABLE

Four point shipyard lifting cage with connections at 65" requiring no steps to connect rigging
Certified lifting eyes with certification printed on unit

POWER SOURCE

460 Volt, 3Phase, 15 horsepower direct drive, high output motor. Maximum amperage draw 123.

QUIET OPERATION

Below 83 decibels at 3 meters. 4-in-1 cooling, DH, heat and high pressure blower.

FAN

5,000 CFM - 16" W.C.

CAPACITY

15 ton A/C

45 KW heat with individual 15 KW stages

STANDARD EQUIPMENT

- Powder coated galvanized steel with Nyalic corrosion resistant coating
- Electronic variable CFM
- 5 Levels of variable temperature and humidity settings with a flip of a switch
- Camlok electrical connections with S.S. ground stud
- 12" duct connection
- Continuous duty cycle
- 125 Amp circuit breaker
- Compressor short cycle timer
- Hour meter
- Power phase indicator
- One year warranty
- Corrosion resistant protective coil coating
- Low ambient operation down to 40°F

OPTIONS

- Automated temperature & humidity control
- Portable unit trailer
- Motor voltage protector





RAPID PREP

DH/AC 5000 HP

Weight – 3,000 lbs.

Height – 67"



Length – 96"

Width – 91"