

## **HURRICANE** 500

- TRAILER MOUNTED: Chassis Tandem 7000# axles, 4" x 6" rectangular tube frame; four, 8 lug P235R- 16 ten ply, radials. DOT lighting with electric brakes.
- **POWER SOURCE:** John Deere turbo-charged diesel engine, 6 cylinder, 170 HP at 2400 RPM.
- P.T.0 (clutch): Twin Disc 11.5"
- VACUUM AIR FLOW (blower): Positive displacement, 2350 CFM capable of 28" Hg, 5 belt driven with guard. (Roots 616 DVJ or equal)
- FILTRATION SYSTEM (3-Stage):
  - Stage 1: Cyclonic separation.
  - Stage 2: Baghouse / 37 Teflon coated, quick change filter bags with continuous reverse pulse air cleaning.
  - Stage 3: High efficiency blower safety filter.
- HYDRAULICS: 3.5 GPM, 2200 PSI, direct driven
- **ENCLOSURE:** Lockable steel shroud over engine. (Fiberglass shroud available)
- INSTRUMENT PANEL (fully enclosed): 12 volt key start, Murphy safety system (low oil pressure/ high water temperature-auto shut down). Gauges: oil pressure, water temperature, ammeter, tachometer with hour meter, filter cleaning on/off switch, material vacuum and dump time controls.
- AIR COMPRESSOR: Direct drive Midland twin cylinder; water cooled and oil pressure fed. Midland air dryer with electronic heater. AMSE certified air tank mounted on vibration isolators. (Provides air to pnuematic controls and the self cleaning filter system.)

#### STANDARD EQUIPMENT

- Paint one color (custom lettering available)
- Wet or dry operation
- Tool box
- Automatic cone vibrator
- 100 gallon fuel tank
- Adjustable pintle hook
- Emergency stop button
- 10" inspection door (Hopper)

### **OPTIONS**

- Spare tire and carrier
- Cold weather package
- HEPA filtration
- Slide gate discharge
- Auxiliary 50 gallon fuel tank
- Hydraulic lift leg to level trailer
- 16" manhole on baghouse
- High reach package for discharge up to 11'
- Asbestos / hazardous waste package

#### **OPTIONS**

- Parking brake
- Fiberglass locking shroud
- Auger in cone
- Auxiliary air hose 120 PSI
- Skid mount
- Hydraulic surge brake
- 4 point certified lifting cage
- 150 HP electric motor

#### **SAFETY FEATURES**

- OSHA approved belt guard
- Remote emergency stop button
- Safety struts for baghouse
- Emergency brake away chain
- Wheel chocks
- Optional HEPA filtration
- Electric brakes
- Low oil or high temp engine shutdown



# **HURRICANE 500**

Raised Height – 18'9"



24'4"