

HURRICANE 500EM

FEATURES

- **SKID MOUNTED:** 4" x 8" rectangular tube frame, fork pockets, and certified lifting cage
- **POWER SOURCE:** 100 HP electric motor, 460 volt, 3-phase, hostile duty (Full Load amps 163, no load 48.8)
- SOUND ATTENUATION PACKAGE: Dual inlet and discharge silencers with sound attenuation enclosure
- VACUUM AIR FLOW (blower): Roots Dresser 2350 CFM capable of 27" Hg, 5 belt driven, with guard
- **FILTRATION SYSTEM:** Cyclonic separation. Baghouse 37 Teflon coated, quick change filter bags with continuous reverse pulse air cleaning. High efficiency blower safety filter.
- **INSTRUMENT PANEL (NEMA 3R):** Soft start package, push button on/off switch with indicator light, disconnect lever, air pulse on/off switch, material dump on/off switch.

STANDARD EQUIPMENT

- Paint-one color (custom lettering available)
- Wet or dry operation
- Automatic cone vibrator


OPTIONS

- Slide gate discharge
- 16" manhole on baghouse
- Auger in hopper (cone)
- Hydraulics (lift cylinder)
- HEPA filtration
- Tool box
- Emergency stop button
- Air compressor 120 PSI
- Trailer mounted to DOT standards





HURRICANE 500EM





Weight – 10,000 lbs.



Length - 129"

Stowed Height – 120"